

**CARACTERISTICI TEHNICE PENTRU DEDURIZATOARELE AZURASOFT DIN SERIA BI-BLOC WS1CI**

Model	Debit m <sup>3</sup> /h	Capacitate m <sup>3</sup> x °G	Conexiuni intrare/iesire	Cantitate rasina litri	Consuma sare la regenerare in kg	Dimensiuni		Volum recipient saramura litri
						cm		
	Butoi saramura	Tanc+valva						
AZ-25VT-WS1CI-B	1,5	75	1"	25	3	38x79	25x96	85
AZ-30VT-WS1CI-B	1,8	90	1"	30	3,6	38x80	25x109	85
AZ-35VT-WS1CI-B	2,1	105	1"	35	4,2	38x81	23x142	85
AZ-40VT-WS1CI-B	2,4	120	1"	40	4,8	38x82	25x132	85
AZ-45VT-WS1CI-B	2,7	135	1"	45	5,4	38x83	25x140	85
AZ-50VT-WS1CI-B	3	150	1"	50	6	38x84	25x157	85
AZ-55VT-WS1CI-B	3,3	165	1"	55	6,6	38x85	30x142	85
AZ-60VT-WS1CI-B	3,6	180	1"	60	7,2	50x80	30x142	140
AZ-65VT-WS1CI-B	3,9	195	1"	65	7,8	50x81	30x152	140

AZ-70VT- WS1CI-B	4,2	210	1"	70	8,4	50x82	30x153	140
AZ-75VT- WS1CI-B	4,5	225	1"	75	9	50x83	33x157	140
AZ-80VT- WS1CI-B	4,8	240	1¼"	80	9,6	50x84	33x158	140
AZ-85VT- WS1CI-B	5,1	255	1¼"	85	10,2	50x85	36x152	140
AZ-90VT- WS1CI-B	5,4	270	1¼"	90	10,8	50x86	40x152	140
AZ-95VT- WS1CI-B	5,7	285	1¼"	95	11,4	50x87	40x153	140
AZ-100VT- WS1CI-B	6	300	1¼"	100	12	50x108	40x154	190